

How To Assemble The Pre-lit Palm Tree

(Model# 3259-57C)




1. Locate the three sections of the two trunks. One section for the 5ft. tree and two sections for the 7ft. tree, which will connect together to form the trunk.



2. Locate the 2 tree tops. The smaller one is for 5ft tree and the larger one is for 7ft tree.



3. Locate the two sections of the base and the eight extension poles.



4. Remove the three screws from one side of the base. Join the two sections of the base together and replace the screws. Making sure they are tight as shown above.



5. Insert the extension poles as shown above to make the palms stable.



6. Place the bottom section of the 7ft. trunk so that it lines up with the center rod of the base. Attach the trunk to the base. Make sure not to cover the trunk clamps with the trunk. Attach the eyebolts to the base and tighten the eyebolts on the inside of the tree to the stabilizing rod to make the trunk is secure. Hook the trunk clamps on the base over the frame of the trunk and tighten as shown above.



7. Attach the upper section of the 7ft. trunk to the lower section. Tighten the two eyebolts as shown above.



Clamp

Plastic tie



8. Carefully clamp the connection of the top and lower sections of the trunk. This will help make the trunk secure. The trunk is shown here without the brown wrap for demonstration purposes only. If you do not want to use the clamp, you may also use the plastic tie, which is also included.



9. Place the 5ft. trunk on to the stand following the same instructions use on the 7ft. to attach it to the base



10. There is a wire rod attached to trunk of the 5ft. palm. Connect this rod to the loop on the 7ft. trunk as shown above to steady the trees



11. Place the palm tops on to the correct trunks. Be sure to tighten the eyebolts on the inside of the trunk to secure the top to the trunk.



12. Connect the plug from the top of the 5ft. tree to the trunk.



13. On the 7ft. tree, connect the plug from the upper section into the lower section.



14. Connect the plug from the upper section of the 7ft. tree to the panel jack, which is located on the top section of the tree.



15. Shape the treetop by evenly spreading the green limbs into an arch from the center to the outer end of the limb. Then plug the cords of 5ft. and 7ft. palms into the outlet to light tree. (Remark: please use the burlap clothes which come with the product to cover the tree stand if necessary)



16. The palm tree also comes with 6 yard stakes. These can be used to secure the base of the palm trees for outdoor use.